


Designed for continuous operations, excellent performance and easy maintenance, DAE Clifton series pumps have proven their reliability and durability in demanding areas like construction, mining, tunnelling, quarries, industries and rental applications.

60 Hz

Dewatering Pump

Clifton 4220

High Chrome Dewatering Pump





Shaft Speed : 3450 rpm

Outlet : 100mm, 4in

OUTPUT	HEAD	FLOW
22 kW	Rated : 180 ft (55 m)	Rated : 264 GPM (16.7 L/s)
30 HP	Max : 230 ft (70 m)	Max : 528 GPM (33.3 L/s)

Solid Passage: 0.6 in (15 mm)



unit : mm

Weight : 256kg / 564 lbs

Pump Type	Electric Submersible Pumps	
	3-Phase	
Motor	Type	Induction Motor
	Poles	2 Pole
	Insulation	Class F
	Protector	Circle Thermal Protector
	Starter	D.O.L.
Lubricant	Food Grade (ISO VG32)	
Impeller Type	Opened	
Shaft Seal	Double Mechanical Seal	
	Silicon Carbide VS Ceramic / Carbon	
Bearings	C3 Shielded ball bearings	
Cable		PVC (CSA Certified) / H07BQ-F
		33ft (10m) or longer upon request.
Materials	Pump Casing	Gray Iron
	Impeller	Chromium Iron
	Motor Frame	Gray Iron
	Motor Shaft	Stainless Steel
	Strainer	Stainless Steel
Max. Liquid Temperature	104 F (40 C)	
Max. Submersion Depth	66ft (20m)	
pH Range	pH 5 - pH 8	